






Heavy Insulated, High Temperature Industrial Heating Tape



HTS/Amptek® AMOX™ Heavy Tape Features:

- For use on Conductive (Metal) Surfaces.
- Dry, Non-Hazardous Area Environment
- 4 ft. Hi Temperature Leads w/ Protective Sleeving
- 2-wire, Crimp Ring Lug Leads
- Heavy Braided Cover with Ties on Each End



Cut-Away Configuration	Max Temp	Size		Watts	Leads (1.2M)	Cat. No. (120V)	Cat. No. (240V)	USD
		Imperial	Metric					
AMOX™ High Temp. (1200°F/ 650°C) Heavy Insulated Heating Tape, Medium Watt Density 8.67 WSI								
		0.5" x 4'	1.3 x 120 cm	208	One End	AWD -051-040	AWD -052-040	181.00
		0.5" x 6'	1.3 x 180 cm	312	One End	AWD -051-060	AWD -052-060	186.00
		0.5" x 8'	1.3 x 240 cm	416	One End	AWD -051-080	AWD -052-080	206.00
		0.5" x 10'	1.3 x 300 cm	520	One End	AWD -051-100	AWD -052-100	224.00
		0.5" x 12'	1.3 x 360 cm	624	Each End	AWM-051-120	AWM-052-120	245.00
		0.5" x 16'	1.3 x 480 cm	832	Each End	AWM-051-160	AWM-052-160	294.00
		0.5" x 20'	1.3 x 600 cm	1040	Each End	AWM-051-200	AWM-052-200	343.00
		0.5" x 24'	1.3 x 720 cm	1248	Each End		AWM-052-240	397.00
		0.5" x 32'	1.3 x 960 cm	1664	Each End		AWM-052-320	457.00
		1.0" x 4'	2.5 x 120 cm	416	One End	AWD -551-040	AWD -552-040	219.00
		1.0" x 6'	2.5 x 180 cm	624	One End	AWD -551-060	AWD -552-060	237.00
		1.0" x 8'	2.5 x 240 cm	832	One End	AWD -551-080	AWD -552-080	259.00
		1.0" x 10'	2.5 x 300 cm	1040	One End	AWD -551-100	AWD -552-100	281.00
		1.0" x 12'	2.5 x 360 cm	1248	Each End	AWM-551-120	AWM-552-120	308.00
		1.0" x 16'	2.5 x 480 cm	1664	Each End	AWM-551-160	AWM-552-160	351.00
		1.0" x 20'	2.5 x 600 cm	2080	Each End	AWM-551-200	AWM-552-200	396.00
		1.0" x 24'	2.5 x 720 cm	2498	Each End		AWM-552-240	452.00
1.0" x 32'	2.5 x 960 cm	3328	Each End		AWM-552-320	550.00		
MEDIUM WATT DENSITY								

Silicone Extruded, Rugged Industrial Heating Tape



HTS/Amptek® Rugged ASR Duo-Tape® Features:

- For use on Conductive (Metal) Surfaces.
- Moisture, Non-Hazardous Area Environment
- 4 ft. Silicone Rubber Leads w/ Protective Sleeving
- 2.5 watts/in²

Cut-Away Configuration	Max Temp	Size		Watts	Leads (1.2M)	Cat. No. (120V)	Cat. No. (240V)	USD
		Imperial	Metric					
AMOX™ High Temp. (450°F/ 232°C) Heavy Insulated Heating Tape, Low Watt Density 2.5 WSI								
		0.5" x 6'	1.3 x 180 cm	90	One End	SRD-051-060	SRD-052-060	219.00
		0.5" x 8'	1.3 x 240 cm	120	One End	SRD-051-080	SRD-052-080	239.00
		0.5" x 10'	1.3 x 300 cm	150	One End	SRD-051-100	SRD-052-100	252.00
		0.5" x 12'	1.3 x 360 cm	180	One End	SRD-051-120	SRD-052-120	278.00
		0.5" x 16'	1.3 x 480 cm	240	One End	SRD-051-160	SRD-052-160	330.00
		0.5" x 20'	1.3 x 600 cm	300	One End	SRD-051-200	SRD-052-200	400.00
		0.5" x 24'	1.3 x 720 cm	360	One End	SRD-051-240	SRD-052-240	490.00
		0.5" x 32'	1.3 x 960 cm	480	One End	SRD-051-320	SRD-052-320	578.00
		0.5" x 42'	1.3 x 1280 cm	630	One End	SRD-051-420	SRD-052-420	650.00
		0.5" x 52'	1.3 x 1580 cm	780	One End	SRD-051-520	SRD-052-520	750.00
		1.0" x 6'	2.5 x 180 cm	180	One End	SRD-101-060	SRD-102-060	289.00
		1.0" x 8'	2.5 x 240 cm	240	One End	SRD-101-080	SRD-102-080	321.00
		1.0" x 10'	2.5 x 300 cm	300	One End	SRD-101-100	SRD-102-100	333.00
		1.0" x 12'	2.5 x 360 cm	360	One End	SRD-101-120	SRD-102-120	360.00
		1.0" x 16'	2.5 x 480 cm	480	One End	SRD-101-160	SRD-102-160	403.00
		1.0" x 20'	2.5 x 600 cm	600	One End	SRD-101-200	SRD-102-200	448.00
		1.0" x 24'	2.5 x 720 cm	720	One End	SRD-101-240	SRD-102-240	530.00
1.0" x 32'	2.5 x 960 cm	960	One End		SRD-102-320	620.00		
1.0" x 42'	2.5 x 1280 cm	1260	One End		SRD-102-420	750.00		
1.0" x 52'	2.5 x 1580 cm	1560	One End		SRD-102-520	860.00		
LOW WATT DENSITY								

Longer lead wires: 48" Standard lead wire length for all Tapes. For longer lengths contact HTS/Amptek®

Special Length, Width, Watts or Volts: Heating tapes may be fabricated to operate on all common voltages, from 12 to 480, and with watt densities from 0.1 to 8 WSI. Contact HTS/Amptek® for knowledgeable design assistance. info@heatingtapes.com

HTS/Amptek Company
P.O. BOX 1381
Stafford, TX 77497 USA